

1. Initiator		2. Type of Review		3. RID Number
Name	Kenneth Costello	<input type="checkbox"/>	General Document Review	00200-326
Organization	Intermetrics	<input checked="" type="checkbox"/>	PDR, CDR, ABR , PPR (circle)	
Phone	304 367 8343	<input type="checkbox"/>	Other _____	
Fax	304 367 8223			
5a. Doc. Number	84K00200	6. Doc. Name	System Level Specification (SLS)	
5a. Doc. Revision	Pre-Release 1			
6. Name of RID Team		SLS RID Review Team		
7. Problem				
Requirement 2.2.4.2.6 states that an audible alarm will be provided, but not to who that alarm will go.				
8. Recommendation				
State to who the alarm is provided.				
Hardcopy of Redlines/Comments Attached <input type="checkbox"/>				
9. Impact if recommendation not implemented				
Alarm may sound in an inappropriate area and not be acted upon.				
Initiator - Signature _____ Submission Date _____				
10. Team Recommendation		11. Action Required		
<input type="checkbox"/> Accepted <input checked="" type="checkbox"/> Rejected <input type="checkbox"/> Study <input type="checkbox"/> Withdrawn <input type="checkbox"/> Deferred to CLCS CCB Screening Panel Comments See attachment. RID Team Manager - Signature _____		<input type="checkbox"/> Update Document <input type="checkbox"/> Study <input type="checkbox"/> Other (specify) _____ Comments 		
12. Final RID Closure Action		13. Additional Comments/Notes		
<input type="checkbox"/> RID to be incorporated in next revision <input type="checkbox"/> RID to be incorporated in other (specify) RID Team Manager - Signature _____				

Due **NO LATER THAN** May 7, 1997

Response Attachment 200-326

The RID Management Team does not agree that the proposed change(s) provide a valid clarification nor satisfy a system specification omission. The requirement states that System Message Viewer is required to provide an audible warning capability. The RID is therefore rejected. Thank you for reviewing the SLS and submitting your RID. Even though we rejected this RID, your input is valuable and we appreciate it.

Additional Information

System Message Viewers only run at an HCI on request by the user at that workstation. The audible queue is local to that workstation. This definition will be presented in product level specifications that are reviewed at CLCS Design Panels. The Redstone version of the System Message Viewer has already been to the Design Panel.